

LIGHT METER

pocket

Model : LX-101

ISO-9001, CE, IEC1010

www.yalab.com.tw 02-2389-0101



Lutron

www.YaLAB.com.tw

The Art of Measurement

LIGHT METER

Model : LX-101

www.YaLAB.com.tw 02-2389-0101

FEATURE

- * Sensor used the exclusive photo diode & multi-color correction filters, spectrum meet C. I. E. standard.
- * Sensor COS correction factor meet standard.
- * Separate LIGHT SENSOR allows user take measurements of an optimum position.
- * Precise and easy readout, wide range.
- * High accuracy in measuring
- * Built-in low battery indicator.
- * LSI-circuit use provides high reliability and durability.
- * LCD display provides low power consumption.
- * Compact, light-weight, and excellent operation.
- * LCD display can clearly read out even of high ambient light.

GENERAL SPECIFICATION

Display	13 mm (0.5") LCD.
Ranges	0-50,000 Lux. 3 Ranges.
Zero adjustment	Internal adjustment .
Over-input	Indication of " 1 ".
Sampling time	0.4 second .
Sensor structure	The exclusive photo diode & color correction filter.
Operating Temp.	0 to 50°C (32 to 122 °F).
Operating Humidity	Less than 80% R.H.
Power Supply	DC 9V battery. 006P,MN1604 (PP3) or equivalent.
Power Consumption	Approx. DC 2 mA.
Dimension	Main Instrument :108x73x23 mm (4.3x2.9x0.9 inch Sensor probe:82x55x7 mm (3.2x2.2x0.3 inch).
Weight	160g (0.36 LB) with batteries.
Accessories Included	Instruction manual..... 1 PC. Carrying case 1 PC.

ELECTRICAL SPECIFICATIONS (23± 5 °C)

Range	Resolution	Accuracy
2,000 Lux	1 Lux	± (5 % + 2 d)
20,000 Lux	10 Lux	± (5 % + 2 d)
50,000 Lux	100 Lux	± (5 % + 2 d)

Note : Accuracy tested by a standard parallel light tungsten lamp of 2856K temperature.

* Appearance and specifications listed in this brochure are subject to change without notice.

LX-101+0603

www.YaLAB.com.tw 02-2389-0101

LX-101 LIGHT SENSOR SPECTRUM

