

ACC., Velocity, Displacement

# VIBRATION METER

Model : VB-8220

ISO-9001, CE, IEC1010

[www.yalab.com.tw](http://www.yalab.com.tw)

02-2389-0101



**Lutron**

[www.YaLAB.com.tw](http://www.YaLAB.com.tw)

*The Art of Measurement*

Acceleration/Velocity/Displacement

# VIBRATION METER

Model :VB-8220

## FEATURES

* Applications for industrial vibration monitoring : All industrial machinery vibrates. The level of vibration is a useful guide to machine condition. Poor balance, misalignment & looseness of the structure will cause the vibration level increase, it is a sure sign that the maintenance is needed.
* Frequency range 10 Hz - 1 kHz, sensitivity relative meet ISO 2954.
* Professional vibration meter supply with vibration sensor and magnetic base, full set.
* Velocity measuring range : 200 mm/s.
* Acceleration measuring range : 200 m/s <sup>2</sup>
* Displacement measuring range : 2 mm ( p-p ).
* RMS & Peak measurement.
* Wide frequency range.
* Data hold button to freeze the desired reading.
* Memory function to record maximum and minimum reading with recall.
* Separate vibration probe, easy operation
* RS 232 computer interface.
* Optional data acquisition software for data record & datalogger.
* Super large LCD display.
* Microcomputer circuit, high performance.
* Auto shut off saves battery life.
* Built-in low battery indicator.
* Heavy duty & compact housing case.
* Complete set with the hard carrying case.

## SPECIFICATIONS

Display	61 mm x 34 mm supper large LCD display. 15 mm ( 0.6" ) digit size.
Measurement	Velocity, Acceleration, Displacement, RMS value, Peak value, Data hold, Max. & Min. value.
Range	Velocity : 200 mm/s : 0.5 to 199.9 mm/s
	Acceleration : 200 m/s <sup>2</sup> : 0.5 to 199.9 m/s <sup>2</sup>
	Displacement ( p-p ) : 2 mm : 0.005 to 1.999 mm * p-p : Peak to Peak

Frequency range	10 Hz to 1 KHz * Sensitivity relative during the the frequency range meet ISO 2954.	
Accuracy	± ( 5 % + 5 d ) reading , 160 Hz, 80 Hz. * 23 ± 5 ℃	
Calibration point	Velocity	50 mm/s ( 160 Hz )
	Acceleration	50 m/s <sup>2</sup> ( 160 Hz )
	Displacement ( p-p )	0.05 mm ( 160 Hz )
Circuit	Exclusive microcomputer circuit.	
Data hold	Freeze the desired reading.	
Peak measurement	To measure the peak value.	
Memory	Maximum & Minimum value.	
Power off	Auto shut off, saves battery life, or manual off by push button.	
Sampling time	Approx. 1 second.	
Data output	RS 232 serial output.	
Operating temperature	0 to 50 ℃ ( 32 to 122 ℉ ).	
Operating humidity	Less than 80% RH.	
Power supply	Alkaline or heavy duty type, DC 9V battery, 006P, MN1604 (PP3) or equivalent.	
Power consumption	Approx. DC 8 mA.	
Weight	Meter	230 g/0.50 LB
	Probe with magnetic base	110 g/0.24 LB
Dimension	Meter : 180 x 72 x 32 mm ( 7.1 x 2.8 x 1.3 inch ). Vibration sensor probe: Round 18 mm Dia. x 40 mm.	
Accessories included	Instruction manual..... 1 PC. Vibration sensor..... 1 PC. Cable..... 1 PC. Magnetic base..... 1 PC. Carrying Case..... 1 PC.	
Optional accessories	* Software ( Windows version, data record & data acquisition ) .....SW-U801-WIN * RS232 cable..... UPCB-01 * USB cable..... USB-01	

\* Appearance and specifications listed in this brochure are subject to change without notice.

VB8220+1306