

CURRENT CALIBRATOR

Model : CC-422

ISO-9001, CE, IEC1010

www.yalab.com.tw

02-2389-0101



Lutron

www.YaLAB.com.tw

The Art of Measurement

CURRENT CALIBRATOR

Model : CC-422

www.YaLAB.com.tw 02-2389-0101

FEATURE

- * Provide the quality and accuracy of handheld calibrator of precision current source.
- * Portable instrument for calibrating process devices and measuring process signals.
- * Adjustable 0-24 mA current source, 2 ranges.
- * Current calibrator drives loads up to 500 ohms.

GENERAL SPECIFICATION

Display	LCD display, max. display counts 1999. 13 mm (0.5") digit size.
Function	mA Current source, 2 ranges. 0 - 19.99 mA x 0.01 mA. 0 - 24.0 mA x 0.1 mA.
Sampling Time	Approx. 0.4 second.
Operating Temperature	0 °C to 50 °C (32 °F to 122 °F)
Operating Humidity	Less than 80% RH.
Power Supply	006P DC 9V, MN1604/PP3 battery or equivalent. Alkaline type or heavy duty type.
Dimension	185 x 78 x 38 mm (7.3 x 3.0 x 1.5 inch).
Weight	265 g/0.58 LB (including battery).
Accessories Included	Operational manual..... 1 PC. Cable with the alligator pairs (red & black), LN-TL421..... 1 PC.

ELECTRICAL SPECIFICATIONS (23± 5 °C)

Range	Display Resolution	Accuracy
0 - 19.99 mA	0.01 mA	± (0.25 % FS + 1 d)
0 - 24 mA	0.1 mA	± (0.5 % FS + 1 d)

* FS : full scale

* Appearance and specifications listed in this brochure are subject to change without notice.

CC-422+0408

www.YaLAB.com.tw 02-2389-0101