

Carbon dioxide, Humidity, Temp., NDIR, 0 to 4,000 ppm, RS232

# CO 2 METER

Model : GCH-2018

ISO-9001, CE, IEC1010

[www.yalab.com.tw](http://www.yalab.com.tw)

02-2389-0101



**Lutron**

[www.YaLAB.com.tw](http://www.YaLAB.com.tw)

*The Art of Measurement*

# CO2 METER + Humidity, Temperature

Model : GCH-2018

[www.YaLAB.com.tw](http://www.YaLAB.com.tw) 02-2389-0101

## FEATURE

* NDIR method principal for CO2 ( Carbon dioxide ) measurement, available for long term operation.
* High repeatability and high accuracy.
* Two probes, one is for CO2/Temp. measurement, the other probe is for Humidity/Temp./Dew point measurement.
* Separate probe, easy operation and convenient for remote measurement.
* CO2 function with alarm setting.
* Humidity measurement with fast response time.
* Large S-TN LCD, high contrast, easy readout.
* Data hold function for freezing the desired value on display.
* Records Maximum and Minimum readings with Recall.
* RS232/USB computer interface.
* Microprocessor circuit assures maximum possible accuracy, provides special functions and features.
* Heavy duty & compact housing with hard carrying case, designed for easy carry out & operation.
* Auto shut off is available to save battery life.
* Power supply from batteries or DC 9V adapter in.

## GENERAL SPECIFICATION

Circuit	Custom one-chip of microprocessor LSI circuit.
Display	LCD size : 52 mm x 38 mm dual function LCD display.
Measurement	CO2 ( Carbon dioxide ), Temp. Humidity, Dew point, Temp.
Unit	CO2            ppm Humidity       % RH Dew point      °C, °F Temp.           °C, °F
Response Time	CO2 :< 2 min. typically. <i>@ Reach the 63% reading value @ Depend the environment air circulation.</i> Humidity/Dew point :10 to 30 seconds typically. <i>@ Reach the 85% reading value @ Depend the environment air circulation.</i>
CO2 altitude compensation setting	0 to 9,000 meters.
Temperature Compensation	Automatic temp. compensation.
Advanced setting	CO2 altitude value setting CO2 alarm value setting °C/°F setting Auto power off enable/disable setting
Alarm setting	For CO2 measurement only.
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.
Display Sampling Time	Approx. 1 second.
Power off	Auto shut off saves battery life or manual off by push button.
Data Output	RS 232/USB PC serial interface. <i>*Connect the optional RS232 cable UPCB-02 will get the RS232 plug.</i> <i>*Connect the optional USB cable USB-01 will get the USB plug.</i>

Probes no.	Two probes : *Probe 1 is for CO <sub>2</sub> , Temp. measurement. *Probe 2 is for Humidity, Dew point. Temp. measurement.
Operating Temperature	0 to 50 °C.
Operating Humidity	Main instrument : Less than 85% R.H.
	CO <sub>2</sub> probe : Less than 85% R.H.
	Humidity probe : 0 to 95 %RH.
Power Supply	DC 1.5 V battery ( UM3, AA ) x 6 PCs, or equivalent.
Power Current	CO <sub>2</sub> measurement
	Approx. DC 9.6 mA for 90% period. Approx. DC 128 mA for 10% period.
	Humidity measurement Approx. DC 5.6 mA.
Weight	Main instrument : 372 g/0.82 LB. @ Battery is included.
	CO <sub>2</sub> probe : 158 g/0.35 LB.
	Humidity probe : 82 g/0.18 LB.
Dimension	Main instrument : 173 x 68 x 42 mm (7.9 x 2.7x 1.2 inch)
	CO <sub>2</sub> Probe : 185 x 38 x 26 mm
	Humidity Sensor Probe : 200 x 23 x 19 mm
Accessories Included	Instruction manual. 1 PC CO <sub>2</sub> probe. 1 PC Humidity probe. 1 PC Hard Carrying case. 1 PC
Optional Accessories	ACV to DC 9V adapter RS232 cable, UPCB-02 USB cable, USB-01 Data Acquisition software, SW-U801-WIN

## ELECTRICAL SPECIFICATIONS (23± 5 °C)

### CO<sub>2</sub> ( Carbon dioxide )

CO <sub>2</sub> 23 + 5 °C	Range	0 to 4,000 ppm
	Resolution	1 ppm
	Accuracy	± 40 ppm * ≤ 1,000 ppm.
		± 5% of reading * > 1,000 ppm ≤ 3,000 ppm.
		± 250 ppm typically * > 3,000 ppm, reference only
Repeatability	± 20 ppm * ≤ 3,000 ppm.	
Temperature	Range	0 °C to 50 °C, 32 °F to 122 °F.
	Resolution	0.1 degree
	Accuracy	°C - 0.8 °C, °F - 1.5 °F.

### Humidity/ Temp.

Humidity	Range	10 % to 95 % R.H.
	Resolution	0.1 % R.H.
	Accuracy	≥ 70% RH :± (3% reading + 1% RH). < 70% RH :± 3% RH.
Temperature	Range	0 °C to 50 °C, 32 °F to 122 °F.
	Resolution	0.1 degree
	Accuracy	°C - 0.8 °C, °F - 1.5 °F.

### Dew point

°C	Range	-25.3 °C to 48.9 °C
----	-------	---------------------

	Resolution	0.1 °C
°F	Range	-13.5 °F to 120.1 °F.
	Resolution	0.1 °F.
<i>Remark :</i> * Dew Point display value is calculated from the Humidity/Temp. measurement automatically. * The Dew Point accuracy is sum accuracy value of Humidity & Temperature measurement..		

\* Appearance and specifications listed in this brochure are subject to change without notice.

GCH2018+1808

[www.YaLAB.com.tw](http://www.YaLAB.com.tw)

**02-2389-0101**