MILLIOHM METER

Model: MO-2001 ISO-9001, CE, IEC1010

www.yalab.com.tw 02-2389-0101





The Art of Measurement

MILLIOHM METER

Model: MO-2001 www.YaLAB.com.tw 02-2389-0101

FEATURE

- * 4 terminal devices for accurate measurement of very low resistance.
- * Ideal for measuring the resistance of the motor coil, transformer, PCB layout.
- * Ideal for testing protective conductors, lightning conductors and welded points.
- * Wide measuring range, 0.1 m ohm 2000 ohm, 5 ranges.
- * 18 mm, large size LCD display, easy to read-out.
- * LSI circuit provides high accuracy, reliability and durability.
- * Built-in over input indication.
- * Durable & portable housing plastic case with the front protective cover.

GENERAL SPECIFICATION

Display	18 mm (0.7") LCD (Liquid Crystal Display). Max. indication 1999.			
Range	200 m ohm, 2,000 m ohm, 20 ohm, 200 ohm, 2000 ohm.			
Zero Adjustment	External adjustment for zero value of the display.			
Input Terminal	4 terminal input, accurate for low ohms measuring.			
Over input Indication	Indication of "1".			
Sampling Time	Approx. 0.4 sec.			
Operating Temp.	0 $^{\circ}\mathrm{C}$ to 50 $^{\circ}\mathrm{C}$ (32 $^{\circ}\mathrm{F}$ to 122 $^{\circ}\mathrm{F}$).			
Operating Humidity	Less than 80 % R.H			
Power Supply	AC 110V 15%, 50/60 Hz or AC 220V/240V 15%, 50/60 Hz.			
Power Consumption	Approx. 2 VA.			
Dimension	160 x 120 x 85 mm, with housing front cover.			
Weight	Approx. 680 g (1.5 LB).			
Standard Accessories	Power cable 1 PC.			
	4 wire with 2 clips 1 pair			
	Instruction Manual 1 PC.			

ELECTRICAL SPECIFICATIONS $(23\pm5 ^{\circ}C)$

Range	Resolution	Test current	Accuracy	Open circuit voltage
200 m ohm	0.1 m ohm	100 mA	± (0.75% + 4 d)	Approx. 3.8 V DC
2000 m ohm	1 m ohm	10 mA	± (0.75% + 2 d)	Approx. 3.4 V DC
20 ohm	10 m ohm	10 mA		Approx. 3.4 V DC
200 ohm	0.1 ohm	1 mA		Approx. 3.2 V DC
2000 ohm	1 ohm	1 mA		Approx. 3.2 V DC

emark:

When order the MILLIOHM METER, should inform the power supply type is AC 110V, 220 V/240 V, the other should indicate the plug type(USA, GERMANY...) of the power cord.

MO-2001+1708

^{*} Appearance and specifications listed in this brochure are subject to change without notice.