

all in one

MOISTURE METER

Model : PMS-713

ISO-9001, CE, IEC1010

www.yalab.com.tw

02-2389-0101



Lutron

www.YaLAB.com.tw

The Art of Measurement

all in one

MOISTURE METER

Model : PMS-713

www.YaLAB.com.tw 02-2389-0101

FEATURE

- * Designed to check the moisture level of wood, concrete, and other non-wood material.
- * 6 % to 40 % moisture range on wood.
- * 0 to 100% relative moisture value for Concrete and other non-wood material.
- * All in one, meter build in the test pins.
- * Data hold function to freeze the desired value on display.
- * Microprocessor circuit ensures high accuracy and provides special functions and features.
- * Operates from DC 1.5V (UM4/AAA) x 4 PCs batteries.
- * Built-in low battery indicator.
- * With the pins' protection cover.
- * Durable, long-lasting components, enclosed in strong, compact ABS-plastic housing.

SPECIFICATION

Applications	Designed to check the moisture level of wood,concrete and other non-wood material.
Measuring Principal	Used the 2 pins electrode to measure the conductive ability of the species, then converter to the reading of % " Moisture of Content " .
Display	LCD size : 28 mm x 19 mm.
Material/ Range	Material 1 :0 to 100% relative moisture value for Concrete. and other non-wood material. Material 2 : 6 % to 40 % moisture range on wood.
Resolution	0.1 %.
Accuracy	$\pm (5 \% + 5 d)$ @ 23 \pm 5 $^{\circ}$ C @ Material 1 : 13 % to 100% @ Material 2 : 6 % to 40%
Circuit Probe	Custom one-chip of microprocessor LSI circuit. 2 pins moisture electrode.
Data Hold	Freeze the display reading.
Sampling Time	Approx. 0.8 second.
Operating Temp.	0 to 50 $^{\circ}$ C .
Operating Humidity	Less than 80% R.H.
Power Supply	DC 1.5 V battery (UM4/AAA) x 4 PCs,
Power Current	Approx. DC 12 mA
Weight	180 g/ 0.40 LB.@ Battery is included.
Dimension	180 x 40 x 40 mm (7.1" x 1.6" x 1.6")
Accessories Included	Instruction manual.....1 PC. Extra test pins..... 1 Set.
Optional Accessory	* Soft carrying case with sash (210 x 80 x 50 mm), Model : CA-52A * Test pins , MP-02

* Appearance and specifications listed in this brochure are subject to change without notice.

PMS-713+0705