

Mini pocket type, Emissivity adj., Laser target light
INFRARED THERMOMETER

Model : TM-958

ISO-9001, CE, IEC1010

www.yalab.com.tw 02-2389-0101



Lutron

The Art of Measurement

www.YaLAB.com.tw

Laser Target Light

INFRARED THERMOMETER

Model : TM-958

FEATURES	
* Infrared thermometer, non-contact temperature measurement, -30 to 300 °C (-22 to 572 °F), precision for none contact temperature measurement.	* Emissivity value can adjust from 0.2 to 1.00. * Back light LCD display. * LCD display both temperature and the emissivity value.
* Microcomputer circuit with high performance.	* Laser target guide for IR thermometer.
* Wide temperature measuring range.	* 0.5 degree display resolution.
* Measurement via one operation button, easy to operate.	* Auto power shut off saves battery life. * Built-in low battery indicator.
* Build in °C & °F select switch.	* Compact housing case with stand.
* Automatic data hold.	* Operates from 006P DC 9V battery.
* 0.95 default emissivity value.	

GENERAL SPECIFICATIONS

Display	LCD, 29 mm x 33 mm. * Main display to show temp. value. * Lower display to show emissivity value. * Back Light.	Sampling Time	Approx. 0.6 second.
Functions	°C, °F, Auto data hold, Auto power off, Auto LCD back light, Emissivity adjustment.	Hold and Auto Power Off function	After release the operation switch, display will hold the last measuring value within 5 seconds continuously.
		Over Indication	≥ 305 °C, display will show 350 °C and flashed. ≤ -30 °C, display will show -30 °C and flashed.
		Power Supply	DC 9V battery, 006P, MN1604 (PP3) or equivalent, heavy duty or Alkaline.
Measurement Range	-30 to 300 °C (-22 to 572 °F),	Power Consumption	Approx. DC 14 mA, with laser light out. Approx. DC 25 mA, w/o laser light out.
Resolution	0.5 °C/0.5 °F.	Operating Temp. and Humidity	0 to 50 °C (32 to 122 °F). Less than 80% RH.
Circuit	Exclusive microcomputer circuit.	Weight	140 g/0.3 LB (without battery).
Emissivity Adjustment	Adjustment range : 0.20 to 1.00. * 0.95 default emissivity value.	Dimension	160 x 92 x 45 mm. (6.3 x 3.6 x 1.8 inch).
Target Guide	* Less than 1 mW. * Class 2 laser diode. Red. Wave length is 645 nm approximately.	Standard Accessory	Operational manual..... 1 PC.

ELECTRICAL SPECIFICATIONS

Measurement Range	-30 to 300 °C (-22 to 572 °F),	Temp. Sensor	Thermocouple pie.
Resolution	0.5 °C/0.5 °F.	Emissivity Setting	* By push button. Setting range : 0.20 to 1.00. * The default emissivity value is 0.95, which will cover 90% of a typical application.
Accuracy	± 3 % of reading or ± 3 °C(5 °F), which ever is greater. * Meter operating temp. within 23 ± 5 °C and the emissivity value of measurement target set to 0.95. * Spec. tested under the 20 cm dia. black body, the measuring distance from the probe sensing Head is 30 cm.	Measurement Wave length Region	6 to 12 micro meter.
		Distance Factor	D/S : Approx. 7:1. D - Distance, S - Spot.

* Appearance and specifications listed in this brochure are subject to change without notice.

0503-TM958

www.YaLAB.com.tw

02-2389-0101